

# Machine for sanitizing floors

# SFO<sup>L</sup>



## COMAC SRO L SANITIZER IS THE PROFESSIONAL SOLUTION FOR SANITIZING FLOORS IN A FAST AND EFFECTIVE MANNER!

A group of nozzles installed at the rear of the machine vaporizes the disinfectant across the entire 100 cm sanitizing path, leaving the surface sanitized.

SRO L Sanitizer effectively sanitizes large surfaces in a short time, up to 106.000 sqm. It can work continuously for 5 hours, and each full tank can contain up to 50 liters of sanitizing liquid. It is compatible with all types of disinfectant.

Protect people's health by ensuring flooring is fully sanitized in: HOSPITALS, HEALTH CENTRES, SUPERMARKETS, CANTEENS, WAREHOUSES, AIRPORTS, STATIONS AND SHOPPING CENTERS.



**SANITIZES UP TO 106.000 SQM OF FLOORING WITH 1 FULL TANK OF DISINFECTANT**



**HAS A SANITIZING PATH OF 1 METER**



**CAN WORK CONTINUOUSLY FOR 5 HOURS**



**YOU CAN CHECK THE ACTIVITY REMOTELY ON MOBILE DEVICES VIA THE MY.FLEET APP**


CFC is the Comac Fleet Management system, which collects the data sent by each machine and translates it into valuable information accessible to you easily in real time, 24/7, from your smartphone, through the app My.Fleet. The My.Fleet app updates you in real time, providing you with all the information you need to keep performance high.

You can see easily from your smartphone or tablet where the machines are located and if they are following the scheduled cleaning program.



**IT CAN BE USED WITH ANY TYPE OF DISINFECTANT SUITABLE for the use with sanitizers\***

\* Please follow the dilution and safety instructions of the disinfectant manufacturer



During the **ORDINARY DISINFECTION PROCEDURE**, environmental surfaces must be decontaminated daily with dedicated disinfectants. In cases of suspected and confirmed infection, the procedure is even more strict. **How long can the novel Coronavirus survive on surfaces?**

A virus can survive for several hours on surfaces.

The use of disinfectants can kill viruses, preventing them from infecting people. A sanitizing machine for large indoor areas enables all flooring to be sanitized with a disinfectant in a very short time.

TECHNICAL DATA		SRO L SANITIZER
Estimated coverage	up to sq.m/h / up to sq.ft/h	5000/53819,55
Estimated coverage (with one full tank)	up to sq.m/sq.ft	106000/1140974,5
Estimated coverage (with one charge of batteries)	up to sq.m/sq.ft	22500/242187,98
Sanitizing width	mm/inch	1000/39,37
Tank with disinfectant	l/gal	51/13,47
Solution flow rate	l/min / gal/min	0,19/0,05
Solution distribution	ml/sq.m	0,481
Compressor	V/W	(1) 24/350
Supply/traction	V	24/aut.
Batteries	(n.) V/Ah C5	(2) 12/105 GEL
Battery run time*	up to h	5
Forward working speed	Km/h	5,5
Maximum gradeability at work at GVW	%	17
Traction motor	V/W	(1) 24/300
Machine dimensions (Lxhwx)	mm/inch	1285x1189x630/50,59x46,81x24,80
Machine weight empty without batteries	Kg/lbs	128/282,19
Machine weight empty with batteries	Kg/lbs	210/462,97
GVW (Gross Vehicle Weight)	Kg/lbs	336/740,75
Sound pressure level	dB (A)	<70
Minimum aisle turn	mm/inch	1830/72

\* Run times are based on continuous scrubbing run times



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY  
Tel. 045 8774222 - Fax 045 8750303 - [www.comac.it](http://www.comac.it) - [com@comac.it](mailto:com@comac.it)

Organisation certified by Q.C.B. Italia ISO 9001:2015, ISO 14001:2015, OHSAS 18001:2007

